


Type 12 Modular Console Cabinet 1472 Series

Sloped Front



Note: This product line will soon be discontinued as a stocked series. Available while quantities last. For alternative solution assistance, please contact Hammond Customer Service - sales@hammfg.com or USA (716) 630-7030, Canada and International (519) 822-2960.



Application

- Designed to house electrical, electronic, hydraulic or pneumatic controls and instruments.
- Heavy-duty construction provides protection from dirt, dust, oil and water. Sloping front control and instrument panels provide an ideal surface for mounting operator controls or instrumentation.
- Interior mounting is provided for with a removable inner panel located on the rear of the basic console.

Standards

- UL 508 Type 12
- CSA Type 12
- **Complies with**
 - NEMA Type 12
 - IEC 60529, IP65

Construction

- Formed 14 gauge steel.
- Smooth, continuously welded seams, without knockouts, cutouts or holes.
- Sloped front instrument panel is continuously hinged on the front (bottom) edge and secured with captive panel screws, threaded into sealed wells.
- Front instrument panel may be removed by pulling the hinge pin.
- Flush doors are secured with a three point latch and operated with a key locking automotive type handle.
- Two door model has overlapping front doors, with three point latch on right door.
- Oil resistant gaskets are permanently secured and mechanically retained.
- Includes a removable inner panel formed from 12 gauge steel, mounted to the back of the enclosure interior.
- Collar studs are provided for mounting inner panels.
- A bonding stud is provided on the door and a grounding stud is provided in the enclosure for each door.
- A literature pocket is provided.

Finish

| | | | | | | | | | | | | |
|----------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 1472-24 | 13.96 | 23.18 | 12.50 | 21.50 | 14.91 | 23.18 | 13.37 | 21.62 | 12.31 | 20.18 | 10.75 | 18.62 |
| 1472-36 | 13.00 | 35.18 | 11.50 | 33.50 | 19.18 | 35.18 | 17.62 | 33.62 | 16.31 | 32.18 | 14.75 | 30.62 |
| 1472-48 | 13.00 | 47.18 | 11.50 | 45.50 | 19.18 | 47.18 | 17.62 | 45.62 | 16.31 | 44.18 | 14.75 | 42.62 |

Turret

| Part No. | B | F | G | H | Ship Wt. lbs |
|-----------------|-------|-------|-------|------|--------------|
| 1472-24T | 24.00 | 5.00 | 16.00 | 3.00 | 34 |
| 1472-36T | 36.00 | 10.00 | 20.00 | 6.00 | 68 |
| 1472-48T | 48.00 | 10.00 | 20.00 | 6.00 | 80 |

Writing Surface

| Part No. | Width | Depth | Height | Ship Wt. lbs. |
|-----------------|-------|-------|--------|---------------|
| 1472-24W | 24.00 | 10.00 | 4.00 | 9 |
| 1472-36W | 36.00 | 10.00 | 4.00 | 14 |
| 1472-48W | 48.00 | 10.00 | 4.00 | 20 |

Data subject to change without notice.

© 2012. Hammond Manufacturing Ltd. All rights reserved.