

Lite Duty Welded Steel 2-Post Open Frame Rack

DNRRLDW Series

Front 10-32 Tapped Rails





Features

- Constructed in welded 12-gauge steel.
- 44U 83.12" Overall Height.
- 19" EIA-310-D compliant 10-32 front tapped rails.
- One (1) bonding stud located inner bottom of rail.
- Includes large base for freestanding support of equipment.
- Finished in smooth black powder paint.
- Rails and Base packaged in heavy duty cardboard to prevent freight damage.
- Suggested load capacity of 1,200 lb.
- RoHS EU Directive 2002/95/EC compliant.
- Manufactured by Hammond Manufacturing, an ISO 9001:2008 certified company, located in North America.

Accessories

- <u>Two Post Mounting Cantilever Shelf</u>
- Two Post Mounting Clamping Shelf
- <u>Two Post Mounting Deep Channel</u> **Battery Shelf**
- Two Post Mounting Deep Channel **Monitor Shelf**
- <u>Hinged Acrylic Door Panel Cover</u>
- Outlet Strips
- 10-32 Nickel Rack Screw with Plastic 10-32 Black Rack Screw with Nylon Cup Washer
- Small Head 10-32 Thumb Screw
- Rack Panels

- Two Post Mounting Adjustable Shelf
- Two Post Centered Shelf
- Two Post Mounting Keyboard & **Monitor Shelf**
- Two Post Mounting Adjustable Depth DIN Rail
- Cable Management
- 10-32 Black Rack Screw with Nylon Washer
- Washer and Pilot Point
- Grounding
- Rack Unit Label

	Overall Dimensions			Mounting Dimensions			Shipping
Part No.	Height	Width	Depth	Height	Width	Rack Units	Weight
DNRR42LDW	44.60	20.00	19.78	42.00	19.00	24U	38
DNRR63LDW	65.60	20.00	19.78	63.00	19.00	36U	41
DNRR70LDW	72.60	20.00	19.78	70.00	19.00	40U	42
DNRR77LDW	79.60	20.00	19.78	77.00	19.00	44U	45
DNRR84LDW	86.60	20.00	19.78	84.00	19.00	48U	47