






PERFORMANCE SPECIFICATION	MIN	TYP	MAX	UNITS
Lower Frequency:			3345	MHz
Upper Frequency:	3955			MHz
Tuning Voltage:	2.5		23.5	VDC
Supply Voltage:	9.5	10.0	10.5	VDC
Output Power:	0	+3.5	+7.0	dBm
Supply Current:			50	mA
Harmonic Suppression (2 nd Harmonic):			-15	dBc
Pushing:			3.0	MHz/V
Pulling, all Phases:			5.0	MHz pk-pk
Tuning Sensitivity:	25		65	MHz/V
Phase Noise @ 10kHz offset:		-90		dBc/Hz
Phase Noise @ 100kHz offset:		-114		dBc/Hz
Load Impedance:		50		Ω
Input Capacitance:			10	pF
Operating Temperature Range:	-40		+85	$^{\circ}$ C
Storage Temperature Range:	-45		+90	$^{\circ}$ C

Phase Noise (1 Hz BW, Typical)




Tuning Curve (Typical)





TAPE AND REEL



Drawing not to scale

Product Control:

Crystek Part Number:	CVCO55CC-3345-3955	Release Date:	15-Mar-11
Revision Level:	C	Responsible:	C. Vales

Specification is subject to change without notice