

SERIES: VMS-300 | **DESCRIPTION:** AC-DC POWER SUPPLY

FEATURES


- up to 300¹ W continuous power
- 12.5 W/in³ power density
- universal input (90~264 Vac)
- 12 V auxiliary fan output
- over voltage, short circuit, and over temperature protections
- built-in active PFC function
- efficiency up to 85%



MODEL	output voltage	output current	output power	ripple and noise ³	efficiency
	(Vdc)	max (A)	max (W)	max (%)	min (%)
VMS-300-12	12	12.5	150 ²	1	82
VMS-300-15	15	10	150 ²	1	82
VMS-300-24	24	6.25	150 ²	1	83
VMS-300-36	36	4.167	150 ²	1	84
VMS-300-48	48	3.125	150 ²	1	84
VMS-300-D0512	5	12	140	1	80
	12	6.67		1	
VMS-300-D1224	12	6.67	160	1	85
	24	3.33		1	
VMS-300-12-CF	12	25	300	1	82
VMS-300-15-CF	15	20	300	1	82
VMS-300-24-CF	24	12.5	300	1	83
VMS-300-36-CF	36	8.33	300	1	84
VMS-300-48-CF	48	6.25	300	1	84
VMS-300-D0512-CF	5	24	280	1	80
	12	13.33		1	
VMS-300-D1224-CF	5	13.33	146	1	85
	12	6.667		1	
VMS-300-12-CFS	12	25	300	1	82
VMS-300-15-CFS	15	20	300	1	82
VMS-300-24-CFS	24	12.5	300	1	83
VMS-300-36-CFS	36	8.33	300	1	84
VMS-300-48-CFS	48	6.25	300	1	84
VMS-300-D0512-CFS	5	24	280	1	80
	12	13.33		1	
VMS-300-D1224-CFS	5	13.33	146	1	85
	12	6.667		1	

Notes: 1. Peak power of 600 W within 500 μ s only applies to single output models
 2. Maximum power must not exceed 150 W with convection cooling or up to 300 W with 25 CFM forced air cooling
 3. Measured at 10 kHz ~ 20 MHz, twisted pair with 0.1 μ F ceramic and 22 μ F electrolytic parallel capacitors

PART NUMBER KEY



SINGLE OUTPUT

Open Frame and CF models		
Part # Key	Input	Output
1	molex	dinkle
2	molex	molex
3	howder	dinkle
4	howder	molex

CFS model		
Part # Key	Input	Output
5	IEC320 snap-in	dinkle
6	IEC320 snap-in	molex
7	howder	dinkle
8	howder	molex

DUAL OUTPUT

Open Frame and CF models		
Part # Key	Input	Output
9	molex	howder
10	molex	molex
11	howder	molex
12	howder	howder

CFS model		
Part # Key	Input	Output
13	IEC320 snap-in	howder
14	IEC320 snap-in	molex
15	howder	howder
16	howder	molex

INPUT

parameter	conditions/description	min	typ	max	units
voltage		90		264	Vac
frequency		47		63	Hz
current	at 90 Vac, cold start			5	A
inrush current	at 115 Vac, cold start at 230 Vac, cold start			70 35	A
input fuse	5 A / 350 V inserted in primary				
power factor correction	single output models pass EN61000-3-2 Class D dual output models		0.95		

OUTPUT

parameter	conditions/description	min	typ	max	units
load regulation	single output models dual output models		±1 ±5		% %
transient response	returns to within 1% in <2.5 ms for a 50% load change and the peak transient does not exceed 5%				
start-up time				1	s
hold-up time	at 120 Vac, 80% load	16			ms
adjustability	user adjustable		±5		%
switching frequency	PFC PWM	40 55		66 75	kHz kHz
temperature coefficient			0.25		mV/°C
fan drive	12 Vdc / 300 mA for external fan				

PROTECTIONS

parameter	conditions/description	min	typ	max	units
over voltage protection	latch down and auto restart			130	%
over current protection	auto restart	110		140	%
short circuit protection	auto restart with no damage from a short on any output				
over temperature protection	auto restart	105	110	115	°C

SAFETY & COMPLIANCE

parameter	conditions/description	min	typ	max	units
isolation voltage	primary to secondary at 10 mA for 3 seconds	4,000			Vac
	primary to chassis at 10 mA for 3 seconds	1,500			Vac
	primary to core at 10 mA for 3 seconds	1,500			Vac
safety approvals	UL 60601-1, EN 60601-1, IEC 60601-1				
EMI/EMC	EN 60601-1-2/EN 55022 Class B conducted / radiated, EN61000-3-(2,3), EN 60601-1-2/EN 55024 (IEC 61000-4-(2,3,4,5,6,8,11))				
leakage current	at 264 Vac			0.0003	A
MTBF	according to MIL-HDBK-217F at 30°C	100,000			hours
RoHS compliant	yes				


ENVIRONMENTAL

parameter	conditions/description	min	typ	max	units
operating temperature		0		70	°C
storage temperature		-20		85	°C
operating humidity	non-condensing	5		90	%
storage humidity	non-condensing	5		95	%
vibration	5 ~ 50 Hz, acceleration ± 7.35 m/s*s per axis				

CONNECTORS

parameter	conditions/description	min	typ	max	units
input connector (CN1)	open frame and CF	Mating Molex Part No. 035977-0590 or equivalent (5pin, 3 used), or Terminal Block: Howder M3 screws 3 pin 6.35 mm center Part No. HD-601-3P; PCB Labeling: L=Line; N=Neutral; G=Chassis Ground			
	CFS	IEC320 snap-in mounting type or Terminal Block: Howder HD-602-3P			
output connector (CN2)	single output models	Mating Molex Part No. 035977-0690 Terminal block: Dinkle P830N, M5 screws			
	dual output models	Mating Molex Part No. 035977-0890 Terminal block: Howder HD-816-3P, M3 screws			
output pin assignment	single output models	Dinkle: Pin 1 = V-, Pin 2 = V+ Molex: Pins 1~3 = V-, Pins 4~6 = V+			
	dual output models	Howder: Pin 1 = V2, Pin 2 = RTN, Pin 3 = V1 Molex: Pin 1 = V2, Pin 2~5 = RTN, Pin 6~8 = V1			
logical signal connector (CN3)	Mating JST XHP-4 or equivalent (CHYAO SHIUNN JS-2001-04); Mating Pins: JST SXH-002T-P0.6 FOR AWG 30 to 26				
fan driver connector (FAN1)	Mating connector is JST P/N XHP-3 (3 pins 0.98 pitch) or equivalent (CHYAO SHIUNN JS-2001-03)				

DERATING CURVE



Single Output

Open Frame at 300 W max. with 25 CFM forced air cooling,
at 150 W max. convection
CF up to 300 W max.
CFS up to 300 W max.

Dual Output


Open Frame at 240 W max. with 25 CFM forced air cooling,
at 120 W max. convection
CF up to 300 W max.
CFS up to 300 W max.

MECHANICAL


parameter	conditions/description	min	typ	max	units
dimensions	5 x 3.2 x 1.5 (127 x 81.28 x 38.1 mm)				inch
	6.5 x 3.2 x 1.6 (165.1 x 81.28 x 40.64 mm)				inch
	5 x 3.2 x 2 (127 x 81.28 x 50.8 mm)				inch
weight	open frame			500	g
	CF			600	g
	CFS			650	g

MECHANICAL DRAWING (SINGLE OUTPUT)


units: mm [inches]
tolerance: ±0.50 [±0.020]



CF




CFS




MECHANICAL DRAWING (DUAL OUTPUT)


units: mm [inches]
 tolerance: ±0.50 [±0.020]



CF



CFS



REVISION HISTORY

rev.	description	date
1.0	initial release	08/14/2012
1.01	updated part number key, derating curve, misc. updates	09/24/2012

The revision history provided is for informational purposes only and is believed to be accurate.



Headquarters
 20050 SW 112th Ave.
 Tualatin, OR 97062
800.275.4899

Fax 503.612.2383
 cui.com
 techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.