



## **SAW Components**

### **SAW Rx 2in1 filter**

GSM 850 / GSM 900

<b>Series/type:</b>	<b>B9510</b>
<b>Ordering code:</b>	<b>B39941B9510L310</b>
<b>Date:</b>	<b>July 24, 2009</b>
<b>Version:</b>	<b>2.0</b>




Data sheet




Application

- Low-loss 2in1 RF filter for mobile telephone GSM 850 and GSM 900 systems, receive path (Rx)
- Usable passband:  
 Filter 1 (GSM 850): 25 MHz  
 Filter 2 (GSM 900): 35 MHz
- Unbalanced to unbalanced operation for both filters
- Low amplitude ripple
- Suitable for GPRS class 1 to 12




Features

- Package size 1.8 x 1.4 x 0.68 mm<sup>3</sup>
- Package code QCS10V
- RoHS compatible
- Approx. weight 0.006g
- Package for Surface Mount Technology (SMT)
- Ni, gold-plated terminals
- Electrostatic Sensitive Device (ESD)



Pin configuration

- 1 Input [Filter 1]
- 4 Input [Filter 2]
- 6 Output [Filter 2]
- 9 Output [Filter 1]
- 7,8 To be grounded
- 2,3,5,10 Case-ground





<b>SAW Components</b>	<b>B9510</b>
<b>SAW Rx 2in1 filter</b>	<b>881.5 / 942.5 MHz</b>

Data sheet



**Characteristics of Filter 1 (GSM850)**

Temperature range for specification:  $T = -20\text{ °C to }+85\text{ °C}$   
 Terminating source impedance:  $Z_S = 50\ \Omega$   
 Terminating load impedance:  $Z_L = 50\ \Omega$

		min.	typ. @ 25 °C	max.	
<b>Center frequency</b>	$f_C$	—	881.5	—	MHz
<b>Maximum insertion attenuation</b>	$\alpha_{max}$				
	869.0 ... 894.0 MHz	—	1.5	2.0	dB
<b>Amplitude ripple (p-p)</b>	$\Delta\alpha$				
	869.0 ... 894.0 MHz	—	0.5	1.1	dB
<b>Input VSWR</b>					
	869.0 ... 894.0 MHz	—	1.8	2.1	
<b>Output VSWR</b>					
	869.0 ... 894.0 MHz	—	1.7	2.1	
<b>Attenuation</b>	$\alpha$				
	10.0 ... 447.0 MHz	45	48	—	dB
	447.0 ... 849.0 MHz	30	35	—	dB
	914.0 ... 1000.0 MHz	25	30	—	dB
	1000.0 ... 1738.0 MHz	28	36	—	dB
	1738.0 ... 1788.0 MHz	35	39	—	dB
	1788.0 ... 3476.0 MHz	25	29	—	dB
	3476.0 ... 6000.0 MHz	15	20	—	dB



<b>SAW Components</b>	<b>B9510</b>
<b>SAW Rx 2in1 filter</b>	<b>881.5 / 942.5 MHz</b>
Data sheet	<b>SMD</b>

**Maximum ratings of Filter 1**

Operable temperature range	T	-40/+85	°C	
Storage temperature range	T <sub>stg</sub>	-40/+85	°C	
DC voltage	V <sub>DC</sub>	5	V	
ESD voltage	V <sub>ESD</sub>	100 <sup>1)</sup>	V	machine model, 1 pulse
Input Power at				
GSM 850, GSM 900	P <sub>IN</sub>	15	dBm	effective power in the on-state, duty cycle 4:8
GSM 1800, GSM 1900	P <sub>IN</sub>	15	dBm	
Tx bands				

<sup>1)</sup> acc. to JESD22-A115A (machine model), 1 negative & 1 positive pulse.



SAW Components

B9510


SAW Rx 2in1 filter

881.5 / 942.5 MHz


Data sheet



**Transfer function Filter 1 (GSM850)**





**Transfer function Filter 1 (GSM850) - Wideband**





Please read *cautions and warnings* and *important notes* at the end of this document.

Smith charts of Filter 1 (GSM850)

**S<sub>11</sub> function**



**S<sub>22</sub> function**





<b>SAW Components</b>	<b>B9510</b>
<b>SAW Rx 2in1 filter</b>	<b>881.5 / 942.5 MHz</b>

Data sheet

**SMD**

**Characteristics of Filter 2 (GSM900)**

Temperature range for specification:  $T = -20\text{ °C to }+85\text{ °C}$   
 Terminating source impedance:  $Z_S = 50\Omega$   
 Terminating load impedance:  $Z_L = 50\Omega$

		min.	typ. @ 25 °C	max.	
<b>Center frequency</b>	$f_c$	—	942.5	—	MHz
<b>Maximum insertion attenuation</b>	$\alpha_{max}$	—	1.6	2.5 <sup>1)</sup>	dB
925.0 ... 960.0 MHz					
<b>Amplitude ripple (p-p)</b>	$\Delta\alpha$	—	0.8	1.8	dB
925.0 ... 960.0 MHz					
<b>Input VSWR</b>		—	1.8	2.1	
925.0 ... 960.0 MHz					
<b>Output VSWR</b>		—	1.9	2.1	
925.0 ... 960.0 MHz					
<b>Attenuation</b>	$\alpha$				
10.0 ... 480.0 MHz		45	48	—	dB
480.0 ... 905.0 MHz		30	34	—	dB
905.0 ... 915.0 MHz		15 <sup>2)</sup>	24	—	dB
980.0 ... 1000.0 MHz		26	34	—	dB
1000.0 ... 1850.0 MHz		28	39	—	dB
1850.0 ... 1920.0 MHz		40	47	—	dB
1920.0 ... 3700.0 MHz		32	36	—	dB
3700.0 ... 6000.0 MHz		28	33	—	dB

1) 2.2 dB max at +25 °C  
 2) 20 dB max at +25 °C



SAW Components

B9510

SAW Rx 2in1 filter

881.5 / 942.5 MHz

Data sheet

**SMD**

### Maximum ratings of Filter 2


Operable temperature range	T	-40/+85	°C	
Storage temperature range	T <sub>stg</sub>	-40/+85	°C	
DC voltage	V <sub>DC</sub>	5	V	
ESD voltage	V <sub>ESD</sub>	100 <sup>1)</sup>	V	machine model, 1 pulse
Input Power at				
GSM 850, GSM 900	P <sub>IN</sub>	15	dBm	effective power in the on-state, duty cycle 4:8
GSM 1800, GSM 1900	P <sub>IN</sub>	15	dBm	
Tx bands				

<sup>1)</sup> acc. to JESD22-A115A (machine model), 1 negative & 1 positive pulse.






Transfer function Filter 2 (GSM900)



Transfer function Filter 2 (GSM900) - Wideband





Please read *cautions and warnings* and *important notes* at the end of this document.

Data sheet



**SMD**

Smith charts of Filter 2 (GSM900)

**S<sub>11</sub> function**



**S<sub>22</sub> function**





<b>SAW Components</b>	<b>B9510</b>
<b>SAW Rx 2in1 filter</b>	<b>881.5 / 942.5 MHz</b>
Data sheet	<b>SMD</b>

## References

<b>Type</b>	B9510
<b>Ordering code</b>	B39941B9510L310
<b>Marking and package</b>	C61157-A7-A153
<b>Packaging</b>	F61074-V8226-Z000
<b>Date codes</b>	L_1126
<b>S-parameters</b>	B9510_LB_NB.s2p B9510_LB_WB.s2p B9510_UB_NB.s2p B9510_UB_WB.s2p See file header for port/pin assignment table.
<b>Soldering profile</b>	S_6001
<b>RoHS compatible</b>	defined as compatible with the following documents: "DIRECTIVE 2002/95/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 27 January 2003 on the restriction of the use of certain hazardous substances in electrical and electronic equipment. 2005/618/EC from April 18th, 2005, amending Directive 2002/95/EC of the European Parliament and of the Council for the purposes of establishing the maximum concentration values for certain hazardous substances in electrical and electronic equipment."

For further information please contact your local EPCOS sales office or visit our webpage at [www.epcos.com](http://www.epcos.com).

**Published by EPCOS AG**  
**Surface Acoustic Wave Components Division**  
**P.O. Box 80 17 09, 81617 Munich, GERMANY**

© EPCOS AG 2009. This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.

Please read *cautions and warnings and important notes* at the end of this document.



## Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous)**. Useful information on this will be found in our Material Data Sheets on the Internet ([www.epcos.com/material](http://www.epcos.com/material)). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, BAOKE, Alu-X, CeraDiode, CSMP, CSSP, CTVS, DSSP, MiniBlue, MiniCell, MKK, MLSC, MotorCap, PCC, PhaseCap, PhaseCube, PhaseMod, PhiCap, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SIMID, SineFormer, SIOV, SIP5D, SIP5K, ThermoFuse, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at [www.epcos.com/trademarks](http://www.epcos.com/trademarks).