

Features

- ✧ Low power loss, high efficiency
- ✧ High current capability, low VF
- ✧ High reliability
- ✧ High surge current capability
- ✧ Epitaxial construction
- ✧ Guard-ring for transient protection
- ✧ For use in low voltage, high frequency inverter, free wheeling, and polarity protection application
- ✧ Green compound with suffix "G" on packing code & prefix "G" on datecode



Mechanical Data

- ✧ Cases: TO-220AB molded plastic
- ✧ Epoxy: UL 94V-0 rate flame retardant
- ✧ Terminals: Pure tin plated, lead free, solderable per MIL-STD-202, Method 208 guaranteed
- ✧ Polarity: As marked
- ✧ High temperature soldering guaranteed: 260°C/10 seconds/.25", (6.35mm) from case
- ✧ Weight: 1.89 grams

Ordering Information(example)

| Part No. | Package | Packing | Packing code | Green Compound Packing code |
|----------|----------|-----------|--------------|-----------------------------|
| SR1620 | TO-220AB | 50 / TUBE | D0 | D0G |

Maximum Ratings and Electrical Characteristics

Rating at 25 °C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%

| Type Number | Symbol | SR 1620 | SR 1630 | SR 1640 | SR 1650 | SR 1660 | SR 1690 | SR 16100 | SR 16150 | Units |
|---|-----------------|---------------|---------|---------|---------|---------------|---------|----------|----------|--------------------|
| Maximum Recurrent Peak Reverse Voltage | V_{RRM} | 20 | 30 | 40 | 50 | 60 | 90 | 100 | 150 | V |
| Maximum RMS Voltage | V_{RMS} | 14 | 21 | 28 | 35 | 42 | 63 | 70 | 105 | V |
| Maximum DC Blocking Voltage | V_{DC} | 20 | 30 | 40 | 50 | 60 | 90 | 100 | 150 | V |
| Maximum Average Forward Rectified Current | $I_{F(AV)}$ | 16 | | | | | | | | A |
| Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method) | I_{FSM} | 170 | | | | | | | | A |
| Maximum Instantaneous Forward Voltage (Note 1) @ 8 A | V_F | 0.55 | | 0.70 | | 0.90 | | 1.05 | | V |
| Maximum D.C. Reverse Current @ $T_A=25\text{ }^\circ\text{C}$ at Rated DC Blocking Voltage @ $T_A=100\text{ }^\circ\text{C}$ | I_R | 0.5 | | | | 0.1 | | | | mA |
| | | 15 | | 10 | | 5 | | | mA | |
| Typical Junction Capacitance (Note 2) | C_j | 440 | | | 320 | | | | | pF |
| Typical Thermal Resistance | $R_{\theta JC}$ | 2.5 | | | | | | | | $^\circ\text{C/W}$ |
| Operating Junction Temperature Range | T_J | - 65 to + 125 | | | | - 65 to + 150 | | | | $^\circ\text{C}$ |
| Storage Temperature Range | T_{STG} | - 65 to + 150 | | | | | | | | $^\circ\text{C}$ |

Note 1 : Pulse Test with PW=300 usec, 1% Duty Cycle

Note 2 : Measured at 1 MHz and Applied Reverse Voltage of 4.0V D.C.

RATINGS AND CHARACTERISTIC CURVES (SR1620 THRU SR16150)

FIG. 1- MAXIMUM FORWARD CURRENT DERATING CURVE




FIG. 2- MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT PER LEG




FIG. 3- TYPICAL FORWARD CHARACTERISTICS PER LEG




FIG. 4- TYPICAL REVERSE CHARACTERISTICS PER LEG




FIG. 5- TYPICAL JUNCTION CAPACITANCE PER LEG





FIG. 6- TYPICAL TRANSIENT THERMAL CHARACTERISTICS




Ordering information


| Part No. | Package | BULK Packing | Packing code | Green Compound Packing code |
|----------|----------|--------------|--------------|-----------------------------|
| SR16xx | TO-220AB | 50 / TUBE | C0 | C0G |
| | TO-220AB | 50 / TUBE | D0 | D0G |

Note: "xx" is Device Code from "20" thru "150".

Dimensions



| DIM. | Unit(mm) | | Unit(inch) | |
|------|----------|-------|------------|-------|
| | Min | Max | Min | Max |
| A | - | 10.50 | - | 0.413 |
| B | 2.62 | 3.44 | 0.103 | 0.135 |
| C | 2.80 | 4.20 | 0.110 | 0.165 |
| D | 0.68 | 0.94 | 0.027 | 0.037 |
| E | 3.54 | 4.00 | 0.139 | 0.157 |
| F | 14.60 | 16.00 | 0.575 | 0.630 |
| G | 13.19 | 14.79 | 0.519 | 0.582 |
| H | 2.41 | 2.67 | 0.095 | 0.105 |
| I | 4.42 | 4.76 | 0.174 | 0.187 |
| J | 1.14 | 1.40 | 0.045 | 0.055 |
| K | 5.84 | 6.86 | 0.230 | 0.270 |
| L | 2.20 | 2.80 | 0.087 | 0.110 |
| M | 0.35 | 0.64 | 0.014 | 0.025 |



Marking Diagram



P/N = Specific Device Code
 G = Green Compound
 YWW = Date Code