




**Features**

- ✧ Low power loss, high efficiency
- ✧ High current capability, low VF
- ✧ High reliability
- ✧ High surge current capability
- ✧ Epitaxial construction
- ✧ Guard-ring for transient protection
- ✧ For use in low voltage, high frequency inverter, free wheeling, and polarity protection application
- ✧ Green compound with suffix "G" on packing code & prefix "G" on datecode



**Mechanical Data**

- ✧ Cases: TO-220AC molded plastic
- ✧ Epoxy: UL 94V-0 rate flame retardant
- ✧ Terminals: Pure tin plated, lead free, solderable per MIL-STD-202, Method 208 guaranteed
- ✧ Polarity: As marked
- ✧ High temperature soldering guaranteed: 260°C/10 seconds/.25", (6.35mm) from case
- ✧ Weight: 1.90 grams

**Dimensions in inches and (millimeters)**

**Marking Diagram**



- SRA20XX = Specific Device Code
- G = Green Compound
- Y = Year
- WW = Work Week

**Maximum Ratings and Electrical Characteristics**

Rating at 25 °C ambient temperature unless otherwise specified.  
 Single phase, half wave, 60 Hz, resistive or inductive load.  
 For capacitive load, derate current by 20%

Type Number	Symbol	SRA 2020	SRA 2030	SRA 2040	SRA 2050	SRA 2060	SRA 2090	SRA 20100	Units
Maximum Recurrent Peak Reverse Voltage	$V_{RRM}$	20	30	40	50	60	90	100	V
Maximum RMS Voltage	$V_{RMS}$	14	21	28	35	42	63	70	V
Maximum DC Blocking Voltage	$V_{DC}$	20	30	40	50	60	90	100	V
Maximum Average Forward Rectified Current	$I_{F(AV)}$	20							A
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	$I_{FSM}$	300							A
Maximum Instantaneous Forward Voltage (Note 1) @ 20A	$V_F$	0.55		0.70		0.92		V	
Maximum D.C. Reverse Current at Rated DC Blocking Voltage	$I_R$	@ $T_A=25^\circ C$					0.1		mA
		@ $T_A=100^\circ C$					-		
		@ $T_A=125^\circ C$					5.0		mA
Typical Thermal Resistance	$R_{\theta JC}$	1.5							°C/W
Operating Junction Temperature Range	$T_J$	- 65 to + 125			- 65 to + 150				°C
Operating Temperature Range - In DC forward mode	$T_J$	$\leq 200$							°C
Storage Temperature Range	$T_{STG}$	- 65 to + 150							°C

Note 1 : Pulse Test : 300 us Pulse Width, 1% Duty Cycle

## RATINGS AND CHARACTERISTIC CURVES (SRA2020 THRU SRA20100)

FIG.1 FORWARD CURRENT DERATING CURVE




FIG. 2 MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 3 TYPICAL FORWARD CHARACTERISTICS




FIG. 4 TYPICAL REVERSE CHARACTERISTICS




FIG. 5 TYPICAL JUNCTION CAPACITANCE




FIG. 6 TYPICAL TRANSIENT THERMAL IMPEDANCE

